



PAXTON PLOW CO

SR 7 SERIES
SOIL RENOVATOR
CONTROLLED TRAFFIC



		19S SR7-500CT	19S SR7-20CT	25S SR7-500CT	25S SR7-20CT	16S SR7-600CT	16S SR7-24CT	20S SR7-600CT	20S SR7-24CT	25S SR7-500CTG	25S SR7-20CTG	20S SR7-600CTG	20S SR7-24CTG
No of Shanks		19	19	25	25	16	16	20	20	25	25	20	20
Shank Spacing		500mm	20"	500mm	20"	600mm	24"	600mm	24"	500mm	20"	600mm	24"
Working Width		9m	30'	12m	40'	9m	30'	12m	40'	12m	40'	12m	40'
Transport Width		5.85m											
		19' 2"											
Shank Protection		Hydraulic Recoil											
Breakout Capacity at Blade		Adjustable up to 2000lb											
Working Depth		Up to 550mm (22")											
Drawbar Power	kW	300+		450+		300+		450+		450+			
	hp	400+		600+		400+		600+		600+			
Frame Size		RHS 150 x 150 x 9mm (6" x 6" x 3/8") Toolbars											
Number of Sections		3											
Section Float		±10° Wing Ground Following											
Wing Lock		Over Centre Wing Fold with Locking Pins											
Linkage		Trailing - Cat IV or V Drawbar											
Depth Wheels		14.00 x 24 Industrial Lug											
Number of Wheels		4											
Wheel Centres		3m	120"	3m	120"	3m	120"	3m	120"	3m	120"	3m	120"
Wing Wheel Centres (Guess Row)		Not Applicable. Wheel Centres are the Same as the Main Frame.								12m	40'	12m	40'