



PAXTON PLOW CO

SR 6 SERIES SOIL RENOVATOR



Model	11S SR 6 - 400	13S SR 6 - 400	17S SR 6 - 400	11S SR 6 - 450	13S SR 6 - 450	17S SR 6 - 450	9S SR 6 - 500	11S SR 6 - 500	15S SR 6 - 500	9S SR 6 - 600	11S SR 6 - 600	
No of Shanks	11	13	17	11	13	17	9	11	15	9	11	
Shank Spacing	420mm			450mm			500mm			600mm		
	16"			18"			20"			24"		
Working Width	4.62m	5.46m	7.14m	4.95m	5.85m	7.65m	4.5m	5.5m	7.5m	5.4m	6.6m	
	15' 2"	17' 11"	23' 5"	16' 2"	19' 2"	25' 1"	14' 8"	18' 1"	24' 7"	17' 9"	21' 8"	
Transport Width	4.84m	5.68m	7.36m	5.2m	6.1m	7.9m	4.8m	5.8m	7.8m	5.6m	6.8m	
	15' 11"	18' 8"	24' 2"	17' 1"	20'	25' 11"	15' 8"	19' 1"	25' 7"	18' 5"	22' 4"	
Shank Protection	Hydraulic Recoil											
Breakout Capacity*	Adjustable up to 2000lb											
Working Depth	Up to 550mm (22")											
Drawbar Power	kW	185+	225+	260+	185+	225+	260+	185+	225+	260+	185+	260+
	hp	250+	300+	350+	250+	300+	350+	250+	300+	350+	250+	350+
Frame Size	RHS 150 x 150 x 9mm (6" x 6" x 3/8") Toolbars											
Linkage	Trailing - Cat IV Drawbar											
Depth Wheels	14.00 x 24 Industrial Lug											
Number of Wheels	2											