



PAXTON PLOW CO

SR 7 SERIES SOIL RENOVATOR



Model	23S SR 7 - 400	29S SR 7 - 400	23S SR 7 - 450	29S SR 7 - 450	21S SR 7 - 500	25S SR 7 - 500	21S SR 7 - 600
No of Shanks	23	29	23	29	21	25	21
Shank Spacing	420mm		450mm		500mm		600mm
	16"		18"		20"		24"
Working Width	9.66m	12.18m	10.35m	13.05m	10.5m	12.5m	12.6m
	31' 8"	39' 11"	33' 11"	42' 9"	34' 5"	41'	41' 4"
Transport Width	6.5m		7m		6.5m		7.5m
	21' 4"		22' 11"		21' 4"		24' 6"
Shank Protection	Hydraulic Recoil						
Breakout Capacity at Blade	Adjustable up to 2000lb						
Working Depth	Up to 550mm (22")						
Drawbar Power	kW	300+	450+	300+	450+	300+	450+
	hp	400+	600+	400+	600+	400+	600+
Frame Size	RHS 150 x 150 x 9mm (6" x 6" x 3/8") Toolbars						
Number of Sections	3						
Section Float	±10° Wing Ground Following						
Wing Lock	Over Centre Wing Fold with Locking Pins						
Linkage	Trailing - Cat IV or V Drawbar						
Depth Wheels	14.00 x 24 Industrial Lug						
Number of Wheels	4						